



**SALES
&
HIRE**

VA 30 S

Electric

Article code	Power
706267	400V, 50HZ

Key features	
Wattage/HP	7,5Kw/10HP
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	6mm/.24"
Depth softer concrete	9mm/.35"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide



DEMONSTRATION
& HOW-TO VIDEOS



Physical parameters		
Weight kg/lbs	706267	222.8/491
Dimensions cm/inch	135×56×109/53×22×43	

Field of application	
<p>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</p> <ul style="list-style-type: none"> • Asphalt and cast asphalt surfaces • Concrete and cement, synthetic stone, floor tiles • Screeds of cement, wood cement, ceramic etc. • Natural stone • Metals • Thermoplastic materials 	
<p>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</p> <ul style="list-style-type: none"> • Latex, rubber, soft plastics and foam materials • Wood, carpets and woven materials 	



DEMONSTRATION
& HOW-TO VIDEOS



VA 30 S

Electric

Article code	Power
707373	230/400V dual, 50HZ

Key features

Wattage/HP	5,5Kw/7.4HP
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	6mm/.24"
Depth softer concrete	9mm/.35"
Production/h	50-55m ² /540sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight	285Kg/628lbs
Dimensions cm/inch	135×56×109/53×22×43

Field of application


Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

Asphalt and cast asphalt surfaces
Concrete and cement, synthetic stone, floor tiles
Screeds of cement, wood cement, ceramic etc.
Natural stone
Metals
Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

Latex, rubber, soft plastics and foam materials
Wood, carpets and woven materials

**SALES
&
HIRE**



DEMONSTRATION
& HOW-TO VIDEOS



VA 30 S

Diesel

Article code	Power
706276	Diesel

Key features

Wattage/HP	6,4Kw / 8.4HP
Working width	30cm / 12"
Distance to wall	9 cm / 3.5"
Depth hard concrete	6 mm / .24"
Depth softer concrete	9 mm / . 35"
Production/h	50-55 m2 / 540 sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight kg/lbs	216 kg / 476 lbs
Dimensions cm/inch	135×56×109 / 53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

- Latex, rubber, soft plastics and foam materials
- Wood, carpets and woven materials

**SALES
&
HIRE**



DEMONSTRATION
& HOW-TO VIDEOS



VA 30 S

Gasoline

Article code	Power
706275	Gasoline

Key features

Wattage/HP	6Kw/8HP
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	6mm/.24"
Depth softer concrete	9mm/.35"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight kg/lbs	173/381
Dimensions cm/inch	135×56×109/53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

- Latex, rubber, soft plastics and foam materials
- Wood, carpets and woven materials



VA 30 SH

Electric

Article code	Power
707199	400V, 50HZ

Key features	
Wattage/HP	7,5Kw
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	7mm/.27"
Depth softer concrete	10mm/.40"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters		
Weight kg/lbs	707199	305.4/673
Dimensions cm/inch	135x56x109/53x22x43	

Field of application	
<p>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</p> <ul style="list-style-type: none"> Asphalt and cast asphalt surfaces Concrete and cement, synthetic stone, floor tiles Screeds of cement, wood cement, ceramic etc. Natural stone Metals Thermoplastic materials 	
<p>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</p> <ul style="list-style-type: none"> Latex, rubber, soft plastics and foam materials Wood, carpets and woven materials 	



VA 30 SH

Diesel with hydraulic traction



Article code	Power
707200	Diesel

Key features	
Wattage/HP	5,6 Kw
Working width	30 cm / 12"
Distance to wall	9 cm / 3.5"
Depth hard concrete	7 mm / .27"
Depth softer concrete	10 mm / .40"
Production/h	50-55 m2 / 540sqf
Standard cutters	Octagonal carbide

Physical parameters	
Weight kg/lbs	273 Kg / 602 lbs
Dimensions cm/inch	135×56×109 / 53×22×43

Field of application	
<p>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</p>	<ul style="list-style-type: none"> • Asphalt and cast asphalt surfaces • Concrete and cement, synthetic stone, floor tiles • Screeds of cement, wood cement, ceramic etc. • Natural stone • Metals • Thermoplastic materials
<p>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</p>	<ul style="list-style-type: none"> • Latex, rubber, soft plastics and foam materials • Wood, carpets and woven materials



VA 30 SH

Diesel with electrostart

Article code	Power
707532	Diesel electrostart

Key features	
Wattage/HP	7,5Kw
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	7mm/.27"
Depth softer concrete	10mm/.40"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters	
Weight kg/lbs	305.4/673
Dimensions cm/inch	135x56x109/53x22x43

Field of application	
<p>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</p>	<ul style="list-style-type: none"> • Asphalt and cast asphalt surfaces • Concrete and cement, synthetic stone, floor tiles • Screeds of cement, wood cement, ceramic etc. • Natural stone • Metals • Thermoplastic materials
<p>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</p>	<ul style="list-style-type: none"> • Latex, rubber, soft plastics and foam materials • Wood, carpets and woven materials

VA 30 SH

Gasoline with hydraulic traction



Article code	Power
707533	Gasoline

Key features

Wattage/HP	8,2 Kw
Working width	30 cm / 12"
Distance to wall	9 cm / 3.5"
Depth hard concrete	7 mm/.27"
Depth softer concrete	10 mm/.40"
Production/h	50-55 m2 / 540sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight kg/lbs	310 Kg / 683 lbs
Dimensions cm/inch	135×56×109 / 53×22×43

Field of application












Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

- Latex, rubber, soft plastics and foam materials
- Wood, carpets and woven materials

Spare parts

Octagonal cutters for VA 30 S / VA 30 SH	Octagonal cutters set 701836		Complete drum 701691		<p>Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings</p> <p>One set contains: 4 flail shafts, 5.0kg washers, 72 pcs octagonal cutters large</p>
Bihexagonal cutters for VA 30 S / VA 30 SH	Hexagonal cutters set 706691		Complete drum 706566		<p>Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings</p> <p>One set contains: 4 flail shafts, 5.0kg washers, 72 pcs bihexagonal cutters large</p>
Beam cutters for VA 30 S / VA 30 SH	Beam cutters set 701839		Complete drum 701694		<p>Application: For removing road markings and paint from asphalt and concrete, and for work on large steel structures with only a slight change of the surface structure</p> <p>One set contains: 4 flail shafts, ca. 5.8kg washers ca. 11.6kg beam cutters large</p>
Milling cutters 19mm for VA 30 S / VA 30 SH	Milling cutters set 701841		Complete drum 701696		<p>Application: For removing and stripping thermoplastic and cold plastic coatings and markings</p> <p>One set contains: 4 flail shafts, 6.0kg washers, 24 pcs milling cutters large</p>
Milling cutters 39mm for VA 30 S / VA 30 SH	Milling cutters set 701840		Complete drum 701695		<p>Application: For removing and stripping thermoplastic and cold plastic coatings and markings</p> <p>One set contains: 4 flail shafts, ca. 6.0kg washers, 12 pcs milling cutters large</p>
Round cutter for VA 30 S / VA 30 SH	Round cutter set 701842		Complete drum 701697		<p>Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings</p> <p>One set contains: 4 flail shafts, 5.9kg washers, 56 pcs round cutters large</p>