



VA30S

Electric

Article code	Power
707373	230/400V dual, 50HZ

Key features	
Wattage/HP	5,5Kw/7.4HP
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	6mm/.24"
Depth softer concrete	9mm/.35"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight 285Kg/628lbs

Dimensions cm/inch 135×56×109/53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

Asphalt and cast asphalt surfaces Concrete and cement, synthetic stone, floor tiles Screeds of cement, wood cement, ceramic etc. Natural stone Metals Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

Latex, rubber, soft plastics and foam materials Wood, carpets and woven materials











Diesel



Article code **Power** 706276 Diesel

Wattage/HP 6,4Kw / 8.4HP Working width 30cm / 12" Distance to wall 9 cm / 3.5" Depth hard concrete 6 mm / .24" Depth softer concrete 9 mm / . 35" Production/h 50-55 m2 / 540 sqf Standard cutters Octagonal carbide

Physical parameters Weight kg/lbs 216 kg / 476 lbs Dimensions cm/inch 135×56×109 / 53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- · Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- · Natural stone

Key features

- Metals
- Thermoplastic materials

Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:

- Latex, rubber, soft plastics and foam materials
- · Wood, carpets and woven materials



🛣 Staybarr House, Kylemore Park North, Ballyfermot, Dublin, D10 WF50



FOLLOW US ON







VA30S

Gasoline

Article code	Power
706275	Gasoline

Key features	
Wattage/HP	6Kw/8HP
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	6mm/.24"
Depth softer concrete	9mm/.35"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight kg/lbs 173/381

Dimensions cm/inch 135×56×109/53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- · Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

- Latex, rubber, soft plastics and foam materials
- · Wood, carpets and woven materials









VA 30 SH

Electric

Article code	Power
707199	400V, 50HZ

Key features	
Wattage/HP	7,5Kw
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	7mm/.27"
Depth softer concrete	10mm/.40"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters

707199 305.4/673 Weight kg/lbs

Dimensions cm/inch 135×56×109/53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

- Latex, rubber, soft plastics and foam materials
- · Wood, carpets and woven materials








VA 30 SH

Diesel with hydraulic traction



Article code	Power
707200	Diesel

Wattage/HP	5,6 Kw
Working width	30 cm / 12"
Distance to wall	9 cm / 3.5"
Depth hard concrete	7 mm / .27"
Depth softer concrete	10 mm / .40"
Production/h	50-55 m2 / 540sqf
Standard cutters	Octagonal carbide

Physical parameters		
Weight kg/lbs	273 Kg / 602 lbs	

Dimensions cm/inch 135×56×109 / 53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- · Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone

Key features

- Metals
- Thermoplastic materials

- Latex, rubber, soft plastics and foam materials
- · Wood, carpets and woven materials







VA 30 SH

Diesel with electrostart

Article code	Power
707532	Diesel electrostart

Key features	
Wattage/HP	7,5Kw
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	7mm/.27"
Depth softer concrete	10mm/.40"
Production/h	50-55m2/540sqf
Standard cutters	Octagonal carbide

Physical parameters

Weight kg/lbs 305.4/673

Dimensions cm/inch 135×56×109/53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- · Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone
- Metals
- Thermoplastic materials

- Latex, rubber, soft plastics and foam materials
- · Wood, carpets and woven materials





VA 30 SH

Gasoline with hydraulic traction



Article code	Power
707533	Gasoline

Wattage/HP	8,2 Kw	
Working width	30 cm / 12"	
Distance to wall	9 cm / 3.5"	
Depth hard concrete	7 mm/.27"	
Depth softer concrete	10 mm/.40"	
Production/h	50-55 m2 / 540sqf	
Standard cutters	Octagonal carbide	

Physical parameters

Weight kg/lbs 310 Kg / 683 lbs

Dimensions cm/inch 135×56×109 / 53×22×43

Field of application

Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:

- · Asphalt and cast asphalt surfaces
- Concrete and cement, synthetic stone, floor tiles
- Screeds of cement, wood cement, ceramic etc.
- Natural stone

Key features

- Metals
- Thermoplastic materials

- Latex, rubber, soft plastics and foam materials
- · Wood, carpets and woven materials





Spare parts

Octagonal cutters for VA 30 S / VA 30 SH	Octagonal cutters set 701836	0	Complete drum 701691	Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings One set contains: 4 flail shafts, 5.0kg washers, 72 pcs octagonal cutters large
Bihexagonal cutters for VA 30 S / VA 30 SH	Hexagonal cutters set 706691		Complete drum 706566	Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings One set contains: 4 flail shafts, 5.0kg washers, 72 pcs bihexagonal cutters large
Beam cutters for VA 30 S / VA 30 SH	Beam cutters set 701839	*	Complete drum 701694	Application: For removing road markings and paint from asphalt and concrete, and for work on large steel structures with only a slight change of the surface structure One set contains: 4 flail shafts, ca. 5.8kg washers ca. 11.6kg beam cutters large
Milling cutters 19mm for VA 30 S / VA 30 SH	Milling cutters set 701841	*	Complete drum 701696	Application: For removing and stripping thermoplastic and cold plastic coatings and markings One set contains: 4 flail shafts, 6.0kg washers, 24 pcs milling cutters large
Milling cutters 39mm for VA 30 S / VA 30 SH	Milling cutters set 701840	3	Complete drum 701695	Application: For removing and stripping thermoplastic and cold plastic coatings and markings One set contains: 4 flail shafts, ca. 6.0kg washers, 12 pcs milling cutters large
Round cutter for VA 30 S / VA 30 SH	Round cutter set 701842	0	Complete drum 701697	Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings One set contains: 4 flail shafts, 5.9kg washers, 56 pcs round cutters large