

MTL 4535 - INDUSTRIAL THREE PHASE



ELECTRONICS





COFFEE, TEA, TOBACCO PROCESSING



TEXTILE



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Low noise level
- ✓ Compact and mobile

- ✓ Reduced downtime of machine tools
- ✓ High filtration efficiency
- ✓ Accessory kit as standard
- ✓ Pressure relief valve for motor protection





















SUCTION UNIT		
Voltage	V - Hz	400 - 50
Power	kW	4
Electrical protection	IP	55
Max water lift	mmH□O	3.200
Max air flow	m³/h	420
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	69
FILTER UNIT		
Filter Type		Star
Surface - Diameter	cm²-mm	20.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Material - Efficiency Air load on filter	IEC 60335-2-69 m ³ /m ² /h	Polyester - ANT M 210
Air load on filter		210
Air load on filter Cleaning system		210
Air load on filter Cleaning system COLLECTION UNIT		210
Air load on filter Cleaning system COLLECTION UNIT Discharge system	m³/m²/h	210 Manual
Air load on filter Cleaning system COLLECTION UNIT Discharge system Capacity	m³/m²/h	210 Manual
Air load on filter Cleaning system COLLECTION UNIT Discharge system Capacity VOLUME	m³/m²/h	210 Manual 45