

GRINDERS / POLISHERS



L3213RE REMOTE-CONTROLLED





& HOW-TO VIDEOS

| 6 | | |
|---|---|--|
| ш | J | |

| Horsepower | 20 HP / 15 KW |
|--|-----------------------------------|
| Voltage (50/60 Hz)* | 3ph x 200-240V |
| Amperage (max)* | 60 Amp |
| Dedicated Breaker Requirement | 80 Amp |
| Generator Recommendation | 45 KW |
| Weight of Machine | 1607 lbs / 729 kg |
| Adjustable Grinding Pressure, Integrated weights with 4 positions | 552-858.7 lbs / 250.5-389.5 kg |
| | |

| integrated weights with 4 positions | 250.5-389.5 kg | |
|--|--------------------------------|--|
| | | |
| Attachment Speed | 400-650 rpm | |
| Working Width | 32in / 814mm | |
| Tool Holder Diameter | 3x13.2in / 3x335mm | |
| Vacuum Hose Port | Camlock E300 | |
| Water feeding (from tank or hose connection) | Under machine | |
| Water tank capacity | 12gal / 46L | |
| Cable Length | 57 ft / 17.4 m | |
| AMG Battery RC Battery (rechargeable) | 12 V/2x7 AH AA 1.2V | |
| Machine Size LxWxH | 97x34x52 in / 246x86x130 cm | |
| Crate size LxWxH | 63x37x63 in / 160x95x160 cm | |

^{*}Also in High Voltage: 3 phase, 380/480V, 32A







| Action required Time left | | | | |
|---------------------------|--------|-------|-------|--|
| Seal Replac | ement | 400 h | Set | |
| Chain Inspe | | 300 h | Set | |
| Belt Inspec | | 400 h | Set | |
| Tooling Inspection | | 200 h | Set | |
| \Diamond | Log in | Lo | g off | |

NEW INTELLIGENT REMOTE CONTROL FOR PRECISE CONTROL OVER THE MACHINE.

INTUITIVE TOUCHSCREEN HMI PROVIDES ESSENTIAL OPERATING INFORMATION AND IMPLEMENTS OPERATOR'S INSTRUCTIONS.

GRINDER CAN BE USED IN 3 MODES: REMOTE-CONTROLLED, SELF-PROPELLED AND MANUAL.