



NP 34

700639

Key features

Needles ø 3 mm	28 pcs. pointed
Air consumption	125 l/min, 4.4 cfm
Max. permitted air pressure	7 bar, 100 psi
Vibration value on handle	6.48 m/s ²
Sound pressure level	< 100.7 db(A)
Acoustic power level	< 110.0 db(A)

Packaging



Case size 475×360×110 mm / 18.7×14.1×4.3"

One case contains

NP 34 needle scaler
 Hose connection G3/8 × 10mm
 VAC Connector
 Auxiliary handle
 2 pcs. of piston seals
 Tube of grease
 Operating manual

Field of application

The unit is intended for machining the surfaces of metal, concrete and stone for the purposes of cleaning, derusting, roughening, descaling, clearing, smoothing and bush-hammering.

Physical parameters

Weight	3.2 kg / 7.0 lbs
Connection thread	G 3/8"

Recommended lubricants

BP	Energol RD-E46
Mobil	Almo Oil 325
Shell	Torcula 100
DEA	Arkas 32
Texaco	Aries 32
Esso	Arox EP 46 or EP 100

Spare parts

Set needles compl.	ø 2 mm. blunt	ø 3 mm. blunt	ø 3 mm. pointed	ø 4 mm. blunt	ø 4 mm. pointed
Article code	706192	706193	706194	706195	706196

